



universität  
wien

Chair for Future Communication  
Prof. Dr. K. Tutschku  
Institute for Distributed and Multimedia Systems  
Faculty for ComputerScience

050069


# VO Netzwerktechnologie für Multimedia Anwendungen

## Lecture 3: Revision of Networking Concepts

Prof. K. Tutschku ([kurt.tutschku@univie.ac.at](mailto:kurt.tutschku@univie.ac.at))

BachelorInformatik (Medieninformatik)  
WS 2010/11

Endowed by





universität  
wien


# A Note on the Use of these PPT Slides

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- ❑ If you use these slides (e.g., in a class) in substantially unaltered form, that you mention their source (after all, we'd like people to use our book!)
- ❑ If you post any slides in substantially unaltered form on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2004  
J.F Kurose and K.W. Ross, All Rights Reserved



*Computer Networking: A Top Down  
Approach Featuring the Internet,  
3<sup>rd</sup> edition.*

Jim Kurose, Keith Ross  
Addison-Wesley, July 2004.

Chair of  
Future Communication

endowed by



Netzwerktechnologie für Multimedia Anwendungen

WS 2010/11



universität  
wien

**And of a from colleague of mine**

**Prof. Dr. Michael Menth (Uni Tübingen),  
thanks a lot!**



Chair of  
Future Communication

endowed by



Netzwerktechnologie für Multimedia Anwendungen

WS 2010/11





## Revision of Networking Concepts

- Overview:
- **Protocol layering and Internet protocol stack**
- **Circuit switching vs. packet switching**
- **Connectionless vs. connection-oriented networks, routing, forwarding, and switching**
- **Transport layer protocols**
- **Application layer**
  - Sockets
  - Client-server and peer-to-peer communication
- **Web services**



## Überblick

- **Das TCP/IP Referenzmodell**
- **Kritik an Referenzmodellen**


Chair of  
Future Communication

endowed by





## The Hourglass Model



Everything  
over IP

IP over  
everything



## Überblick

- Das TCP/IP Referenzmodell
- **Kritik an Referenzmodellen**

Chair of  
Future Communication

endowed by





- **ISO/OSI**

- Unausgeglichene Funktionsfülle der einzelnen Schichten: Presentation Layer, Session Layer, Application Layer
- Hat bei Implementierung in der Praxis versagt
- ITU-T bei der Standardisierung neuer Protokolle langsam

- **TCP/IP**

- Schnelle Verbreitung über BSD/UNIX: gut implementiert, einfach zu benutzen, kostenfrei
- IETF bei der Standardisierung neuer Protokolle schnell
- Spezielle Beschreibung des Status Quo, nicht allgemein

- **5 Schichten-Modell**

- ISO/OSI ohne Session und Presentation Layer
- Meist nützliche und häufig verwendete Taxonomie






- **Gefahr: schränken Denken ein**
- **Erlauben keinen Informationsaustausch zwischen den Schichten**
  - Cross Layer Design (CLD): Austausch von Informationen über möglicherweise mehrere Layer
  - Beispiele für CLD
    - Ausnutzung von Physical Layer Information um Application Layer zu adaptieren bzw. zu optimieren
    - Location-aware Services
    - TCP reagiert auf ECN-bit (explicit congestion notification) in IP Header
- **Einordnung von Protokollen in Schichten manchmal problematisch**
  - TCP/IP/MPLS/SDH/WDM: MPLS gilt als Layer 2.5
  - TCP/IP1/UMTS-Schichten/IP2/ATM/SONET:  
IP kommt im Network und im Link Layer zum Einsatz



## Überblick

- Das TCP/IP Referenzmodell
- Kritik an Referenzmodellen





## Revision of Networking Concepts

- Overview:
- Protocol layering and Internet protocol stack
- **Circuit switching vs. packet switching**
- Connectionless vs. connection-oriented networks, routing, forwarding, and switching
- Transport layer protocols
- Application layer
  - Sockets
  - Client-server and peer-to-peer communication
- **Web services**




# Circuit Switching: FDM and TDM

- Network resources (e.g., bandwidth) **divided into “pieces”**
  - Frequency division multiplex
  - Time division multiplex
  - Pieces allocated to calls
  - Resource piece **idle** if not used by owning call (*no sharing*)

FDM


Frequency

Example: 4 users



Time

Frequency




Time






# Packet Switching




- **Data stream divided into packets**
  - Packet streams of different flows share network resources
  - Each packet uses full bandwidth
  - Resources used as needed
- **Resource contention**
  - Aggregate demand rate can exceed available capacity
  - Congestion: packets queue, wait for link use
- **Store-and-forward: entire packet must arrive at router before it can be transmitted on next link**
- **Example**
  - Link bandwidth  $R=1.5$  Mbit/s
  - Msg size  $L=7.5$  Mbit
  - Takes  $L/R=5$  sec to transmit packet
  - 3 hops  $\Rightarrow$  overall delay = 15 sec

Bandwidth division into “pieces”  
Dedicated allocation  
Resource reservation





# Packet Switching: Statistical Multiplexing



- Sequence of blue and green packets does not have fixed pattern ➡ *statistical multiplexing*
- In TDM each host gets same slot in revolving TDM frame.




# Packet Switching vs. Circuit Switching

- **Comparison**

- Link: 1 Mbit/s
- User
  - 100 kbit/s when “active”
  - Active 10% of time
- Circuit switching: 10 users
- Packet switching: with 35 users, probability > 10 active less than .0004

- **Packet switching allows more users to use network!**



- **Is packet switching better than circuit switching?**
- **Great for bursty data**
  - resource sharing
  - simpler, no call setup
- **Excessive congestion**
  - Packet delay and loss
  - Protocols needed for reliable data transfer, congestion control
- **How to provide circuit-like behavior?**
  - Bandwidth guarantees needed for audio/video apps
  - Still an unsolved problem



## Revision of Networking Concepts


- Overview:
- A picture of the Internet
- Protocol layering and Internet protocol stack
- Circuit switching vs. packet switching
- **Connectionless vs. connection-oriented networks, routing, forwarding, and switching**
- Transport layer protocols
- Application layer
  - Sockets
  - Client-server and peer-to-peer communication
- **Web services**






# Connectionless (Datagram) Networks


- **No call setup at network layer**
  - No network-level concept of “connection”
  - Routers: no per-flow state
- **Packets forwarded using destination host address**
  - But: packets between same source-dest pair may take different paths



1. Send data




2. Receive data






# Connectionless Networks: Routing and Forwarding

- **Routing**
  - Composes forwarding table
  - Distributed routing algorithms
  - Determines route taken by packets from source to dest
- **Forwarding**
  - Moves packets from router's input to appropriate output interface
  - Uses forwarding table
- **Analogy**
  - **Routing**: process of planning trip from source to dest
  - **Forwarding**: process of getting through single interchange



value in arriving packet's header



WS 2010/11



# Connectionless Networks: Longest Prefix Matching

4 billion  
possible entries  
in forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

Prefix Match	Link Interface
11001000 00010111 00010	0
11001000 00010111 00011000	1
11001000 00010111 00011	2
otherwise	3

**Examples:** DA: 11001000 00010111 00010110 10100001  
DA: 11001000 00010111 00011000 10101010

Which interface?

endowed by





# Connectionless Networks: Intra-AS Routing


- **AS: autonomous system**
- **Also known as Interior Gateway Protocols (IGP)**
- **Most common Intra-AS routing protocols:**
  - RIP
    - Routing Information Protocol
    - Distance vector routing protocol based on Bellman-Ford equation
  - OSPF
    - Open Shortest Path First
    - Link state routing protocol, Dijkstra's shortest path algorithm
  - IGRP
    - Interior Gateway Routing Protocol
    - Cisco proprietary
- **IGPs follow usually the shortest paths with regard to a link cost metric**
  - Hop count
  - Latency





# Connection-Oriented Networks (Virtual Circuits)


- **Characteristics of a virtual circuit (VC)**
  - Fixed path from source to destination
  - Packets belonging to VC carry a VC number
  - Forwarding tables along the path keep entry for each VC
- **Connection setup: 3rd important function (next to routing and forwarding) in connection-oriented networks**
- **Signaling protocols for VC setup**
  - Used to setup, maintain, and teardown VC
  - Used in ATM, frame-relay, X.25, in MPLS: RSVP-TE or LDP



5. Data flow begins

4. Call connected


1. Initiate call



6. Receive data

3. Accept call

2. incoming call






# Connection-Oriented Networks: Forwarding Table

- Routers maintain connection state information
- VC number may change on each link

Forwarding table in  
northwest router:



Incoming interface	Incoming VC #	Outgoing interface	Outgoing VC #
1	12	3	22
2	63	1	18
3	7	2	17
1	97	3	87
...	...	...	...



# Connectionless vs. Connection-Oriented Networks

- **Connectionless networks**

- Routers are not flow-aware
- Packets are routed solely based on destination address
- Example: IP datagrams
- Simple operations
- Difficult to add quality of service (QoS)

- **Connection-oriented networks**

- Connections: setup, data transmission, teardown
- Routers keep per connection state
- Explicit paths
  - Deviation from shortest path routing possible
  - Example: label switched paths (LSPs) in MPLS
  - Used for traffic engineering
- Easier support of QoS since flows are known





## Chapter 1: Revision of Networking Concepts


- Overview:
- Protocol layering and Internet protocol stack
- Circuit switching vs. packet switching
- Connectionless vs. connection-oriented networks, routing, forwarding, and switching
- **Transport layer protocols**
- Application layer
  - Sockets
  - Client-server and peer-to-peer communication
- **Web services**





# TCP: Overview RFCs: 793, 1122, 1323, 2018, 2581

- **Point-to-point**
  - One sender, one receiver
- **Flow control**
  - Sender will not overwhelm receiver
- **Congestion control**
  - Sender reduces its rate in case of congested network
- **Connection-oriented**
  - Handshaking (exchange of control msgs) initiates sender, receiver state before data exchange
- **Pipelined**
  - TCP congestion and flow control set window size
- **Send & receive buffers**
- **MSS: maximum segment size**
- **Reliable, in-order byte stream**
  - No “message boundaries”
- **Full duplex data**
  - Bi-directional data flow in same connection
- **Does not provide: timing, minimum bandwidth guarantees**





# UDP: User Datagram Protocol [RFC 768]



- **Very simple, connectionless transmission protocol**
  - No handshaking between UDP sender, receiver
  - Each UDP segment handled independently of others
  - Multicast possible
- **Unreliable data transfer between sending and receiving process**
  - Packet loss
  - Packets delivered out of order to app
- **Does not provide**
  - Connection setup
  - Reliability
  - Flow control
  - Congestion control
  - Timing
  - Bandwidth guarantee
- **Why is there a UDP?**
  - No connection establishment
    - Fast transmission
  - Simple
    - No connection state at sender, receiver
    - Small segment header
  - No congestion control: UDP can blast away as fast as desired



# What Transport Service is Needed?

## Data loss

- ▶ some apps (e.g., audio) can tolerate some loss
- ▶ other apps (e.g., file transfer, telnet) require 100% reliable data transfer

## Bandwidth

- ▶ some apps (e.g., multimedia) require minimum amount of bandwidth to be “effective”
- ▶ other apps (“elastic apps”) make use of whatever bandwidth they get

## Timing

- ▶ some apps (e.g., Internet telephony, interactive games) require low delay to be “effective”



# Transport Service Requirements of Common Apps

Application	Data loss	Bandwidth	Time sensitive
file transfer	no loss	elastic	no
e-mail	no loss	elastic	no
Web documents	no loss	elastic	no
real-time audio/video	loss-tolerant	audio: 5kbps-1Mbps video: 10kbps-5Mbps	yes, 100's msec
stored audio/video	loss-tolerant	same as above	yes, few secs
interactive games	loss-tolerant	few kbps up	yes, 100's msec
instant messaging	no loss	elastic	yes and no



## Internet apps: application, transport protocols

Application	Application layer protocol	Underlying transport protocol
e-mail	SMTP [RFC 2821]	TCP
remote terminal access	Telnet [RFC 854]	TCP
Web	HTTP [RFC 2616]	TCP
file transfer	FTP [RFC 959]	TCP
streaming multimedia	proprietary (e.g. RealNetworks)	TCP or UDP
Internet telephony	proprietary (e.g., Dialpad)	typically UDP





# Stream Control Transmission Protocol (SCTP, RFC2960)

- **High level introduction in RFC3286**
- **Transport protocol**
- **Similarities with UDP**
  - Message-orientation (no byte stream as in TCP)
- **Similarities with TCP**
  - Reliable, in-order delivery
  - Congestion control
- **Multi-streaming**
  - Transmission of several streams over a single SCTP connection, e.g. two images
- **Uses per-stream sequence numbers for messages**
  - If a packet of a specific stream is lost, only this stream suffers from retransmission (no head of the line blocking)
- **Multihoming support**
  - Both sender and receiver may have multiple IP addresses
  - Transparent failover if one of these addresses fails
- **Path selection and monitoring**




# Datagram Congestion Control Protocol (DCCP, RFC4340)

- **Transport protocol**
- **Similarities with UDP**
  - Message-orientation
  - No reliable in-order delivery
- **Similarities with TCP**
  - Connection-orientation
  - Congestion control
- **Makes use of ECN**
- **More appropriate than TCP for realtime data**
  - No retransmissions for in-order delivery
  - Better timeliness for remaining data



# Network Taxonomy



- Networks do not follow either the connection-oriented or connectionless principle
  - Internet provides both connection-oriented (TCP) and
  - Connectionless services (UDP) to apps

- Combinations on different layers possible
  - Packet-switched over circuit-switched
    - IP over optical
  - Circuit-switched over packet-switched
    - ISDN over MPLS



# Where Do Which Principles Apply?



## Internet

- **Connectionless IP datagram forwarding**
- **Transport layer**
  - Connectionless UDP
  - Connection-oriented TCP
- **“Smart” end systems (computers)**
  - Can adapt, perform control, error recovery
  - Simple inside network, complexity at “edge”
- **Consequence of TCP**
  - “Elastic” service
  - No strict timing
- **Many link types**
  - Different characteristics
  - Uniform service difficult

## Asynchronous Transfer Mode (ATM)

- **Connection-oriented ATM cell forwarding**
  - Fixed size cells (48+5 bytes)
  - Virtual path connections (VPCs)
  - Virtual channel connections (VCCs)
  - Today used as link layer below IP
- **Evolved from telephony**
  - Human conversation
  - Guaranteed service needed
  - Strict timing, reliability requirements
- **“Dumb” end systems (telephones)**
  - complexity inside network

## Multiprotocol Label Switching (MPLS)

- Connection-oriented packet forwarding
- Variable size packets
- Often used as link layer below IP
- Simple end-to-end measurements
- Hides network topology from traceroute