

Zur Organisation

- ❑ Zeit: DO 11:05 - 12:35, 13:00-13.45
- ❑ Unterlagen (in *Englisch*)
Kopien der Vorlesungsunterlagen: Anfang November
Folien: TISS –
- ❑ schriftliche Prüfung: 23. 1. 2014

References

1. *Multimedia Programming. Objects, Environments and Frameworks*, S.Gibbs, D.C. Tsichritzis, Addison-Wesley, ACM Press, 1995.
2. *Multimedia: Computing, Communications and Applications*, R.Steinmetz, K.Nahrstedt, 2nd edition, Prentice Hall, 1999.
3. *Video and Image Processing in Multimedia Systems*, B. Furht, S.W. Smoliar, H. Zhang, Kluwer Academic Publishers, 1995.
4. *Image and Video Compression Standards. Algorithms and Architectures*, V. Bhaskaran, K. Konstantinides, 2nd edition, Kluwer Academic Publishers, 1997.

Contents

- ❑ What is a multimedia system? (prologue)
- ❑ Media Types (audio, video, ...)
- ❑ Media Platforms
- ❑ Media Compression (JPEG, MPEG-2, MPEG-4, MP3)
- ❑ MM Programming Abstractions
- ❑ MM Content-Based Information Retrieval und Indexing
- ❑ Content Description (MPEG-7 + MPEG-21)

References

5. *Schall&Klang: Wie und was wir hören*. Georg Eska, Basel; Boston; Berlin; Birkhäuserverlag 1997.
6. *Physikalische und psychoakustische Grundlagen der Musik*. Juan G. Roederer, 3. Auflage, Springer 2000
7. *Fundamentals of Multimedia*. Ze-Nian Li and Mark S. Drew, Prentice Hall, 2004.
8. *The Science of Digital Media*. Jennifer Burg, Pearson Education, 2009.

Prologue: Multimedia—Definitions

- ❑ Multimedia—General Definition
- ❑ Media Classification
- ❑ *Multimedia Systems Definition*

Multimedia—General Definition

- ❑ *Multi-* [lat.: much] many; much; multiple
- ❑ *Medium* [lat.: middle]
 - ❑ an intervening substance through which something is transmitted or carried on; a means for distribution and presentation of information; e.g., atmosphere, water, text, ..
 - ❑ a means of mass communication; e.g., newspaper, magazine, television, ...

Media Classification

- ❑ *Perception media* help humans to perceive their environment. *How do humans perceive information in a computer environment?*
- ❑ *Representation media* are characterized by internal computer representations of information. *How is the computer information coded?*
- ❑ *Presentation media* refer to the tools and devices for i/o of information. *Through which medium is information delivered by the computer, or introduced into the computer?*

Media Classification

- ❑ *Storage media* refer to a data carrier which enables storage of information. *Where will the information be stored?*
- ❑ The *transmission medium* characterizes different information carriers, that enable *continuous* data transmission (storage media excluded!). *Over what will the information be transmitted?*
- ❑ The *information exchange medium* includes all information carriers for transmission, i.e., all storage and transmission media. *Which information carrier will be used for information exchange between different places?*

Representation—Space and Dimension

- ❑ *representation spaces* are part of the presentation media for information output; e.g., movie screen, stereo space
- ❑ each representation space consist of one or more *representation dimensions*; e.g. computer screen (2), stereophony (3)
- ❑ time may occur inside each representation space as additional dimension; *central* to multimedia systems; media are divided into 2 types with respect to time in their information space: *time-independent* and *time-dependent*

Properties of a MM System

- ❑ not every *combination of media* justifies the term *multimedia*; e.g., a text processing program with incorporated images
- ❑ the *level of independence* of different media is important; a computer-controlled VCR vs. a text presentation with synchronized audio
- ❑ *computer-supported integration*—Computer controlled-data of independent media can be processed and integrated by a programmer or multimedia author.

Representation

- ❑ time-independent (discrete) media—information consists exclusively of a sequence of elements or a continuum without any time reference; e.g., text, graphics, ...
 - ❑ time-dependent (continuous) media—information consists of timed sequences, i.e., element values plus time of occurrence; e.g., audio, video, sensor signals, ...
- processing of these media is *time-critical*

Multimedia System—Definition

A multimedia system is characterized by computer-controlled, integrated production, manipulation, presentation, storage and communication of independent information, which is encoded at least through a continuous (time-dependent) and a discrete (time-independent) medium. (Steinmetz/Nahrstedt)

- ❑ MM is often used as an attribute of systems, products, etc., without satisfying the characteristics above. Thus, 2 notions of mm can be distinguished:
 - ❑ mm, strictly speaking (above)
 - ❑ mm, in the general sense used to describe the processing of individual images and text, although no continuous medium is present.

Part I Media Types

Representation, formats and operations of media types

- ☐ Text
- ☐ Graphics (Images)
- ☐ Audio
- ☐ Video

I.1. Media Type Text

Text Representations

- ☐ ASCII / ISO character sets
- ☐ marked-up text — e.g. SGML, HTML, XML, etc.
- ☐ hypertext — e.g. HyperCard, World Wide Web

Text Operations

- ☐ character and string operations
- ☐ editing
- ☐ formatting — interactive, non-interactive, page description languages
- ☐ pattern matching and searching — indexes, signatures
- ☐ sorting
- ☐ compression — Huffman, Lempel-Ziv
- ☐ encryption
- ☐ language specific operations — spelling checking, parsing, statistical analysis of writing style

I.2. Media Type Graphics (Images)

- ☐ Achromatic and Colored Light
- ☐ Intensities
- ☐ Color Models
- ☐ Image Representations
- ☐ Image Formats
- ☐ Image Operations

Light

- ☐ chromatic: of color
- ☐ achromatic: without color (i.e. B&W)
- ☐ color of an object depends upon:
 - ☐ object surface: reflectivity, physical properties, composition
 - ☐ light source(s) illuminating it
 - ☐ color of surrounding environment
 - ☐ visual system (eyes, brain, photoelectric cell, ...) of perceiving entity

Selecting Intensities

- ☐ to find 256 intensities starting with the lowest attainable intensity I_0 and going to a maximum intensity 1.0, with each intensity r -times higher, we use:

$$I_1 = rI_0, I_2 = rI_1 = r^2I_0, I_{255} = rI_{254} = r^{255}I_0 = 1 \quad \text{therefore,}$$

$$r = (1/I_0)^{1/255}, I_j = r^j I_0 = r(1/I_0)^{j/255} I_0$$
- ☐ example: $n=3, I_0 = 1/8$ gives $r=2$ and intensity values of $1/8, 1/4, 1/2$ and 1
- ☐ minimum attainable intensity I_0 for a CRT is between $1/200$ and $1/40$

Achromatic Light

- ☐ black, white, usually greys (rare to see pure black or pure white)
- ☐ quantity or energy of light is only measurement used for achromatic light
 - ☐ intensity, luminance, brightness
 - ☐ scale: $0 = \text{black}, 1 = \text{white}$, greys in between
- ☐ eye is sensitive to ratios of intensity changes, not the changes in intensity values themselves
- ☐ small changes of low intensity seem to have the same effect as larger changes of high intensity
- ☐ dynamic range: ratio between min. and max. intensities

Selecting Intensities

- ☐ how many intensities are enough?
- ☐ answer: r is 1.01 or less, therefore

$$n = \log_{1.01}(1/I_0)$$
- ☐ table on next page shows theoretical values

Dynamic Range

display media	typical dynamic range	number of intensities
CRT	50 - 200	400 - 530
photographic prints	100	465
photographic slides	1000	700
coated paper printed in b/w	100	465
coated paper printed in color	50	400
newsprint printed in b/w	10	234

Halftone Approximation

- ❑ dithering (or half-toning): approximating intensities using dot patterns
 - ❑ human eye generalizes patterns into shades
 - ❑ similar effect with colour: approximate colours using multi-coloured pixel patterns: 8-bit colour graphics does this to "simulate" 24-bit colours (with varying success)
- ❑ simple approach: N device pixels per image point/pixel
 - ❑ create an N by N dither matrix: defines $N \times N + 1$ intensities
 - ❑ to display intensity K, turn on pixels having values $< K$

Different Intensity Levels

intensity levels



2



4



16

Halftone Approximation



0



1



2



3



4


- ❑ cluster dithering: dither intensity centered on middle of matrix
 - ❑ avoid line patterns or other artifacts
 - ❑ patterns should grow - minimizes "contouring" effects
 - ❑ patterns should emanate from centre: effect of increasing dot sizes
- ❑ cluster dithering with diagonal periodicity

Color

- ❑ various models of colour used:
 - ❑ printing & graphics industry: colour sample books and codes
 - ❑ artists: tint (adding white to pure pigment), shade (adding black), tone (adding both)
 - ❑ CRT's: use hardware models, eg. RGB
 - ❑ physicists: use optical models (wavelengths, energy measures)
- ❑ human perception of colour depends on how brain reacts to whole visual environment, as well as brain & eyebiological factors

Color


- ❑ colour is how we perceive beams of electromagnetic energy that fall on our retina
- ❑ we see light between 400 and 700 nanometers in wavelength (10^{-9} meters)



Tristimulus Theory


- ❑ the retina contains cones that sense either red, green, or blue light
- ❑ 6-7 million cones per eye, concentrated in central area called "fovea"
- ❑ rods: sensors that surround fovea, and perceive weak "night" images
- ❑ hence, use indirect vision at night to see low-light images
- ❑ tristimulus theory isn't totally accurate, because many colors we see are not exact combinations of red, green, blue wavelengths

Tristimulus Theory



CIE Color Space

- many combinations of dominant wavelength, luminance, saturation appear the same to us
- CIE color space (Commission Internationale de l'Eclairage) used to calibrate other color models; 1931 CIE XYZ



29

Color

Christian Breiteneder

CIE Color Space


- 100% spectrally pure colors on outer curve edge; pure white near centre (at C)
- if color at A, then B is dominant wavelength: you mix B with C to get A
- F's dominant wavelength defined as the complement of A's ones
- complementary colors: mix together to get white (e.g.. E and D, or F and A)
- can therefore use CIE to:
 - identify and analyze colors
 - measure CRT performance: how much of CIE color space does a particular CRT cover?

30

Color

Christian Breiteneder

CIE Chromaticity Diagram



31

Color

Christian Breiteneder

Color Models for Raster Graphics

1. The RGB color model


- hardware-oriented model that turns on red, green, and blue pixels at varying intensities
- additive: add red, green, blue together to get overall color
- not all colors are exactly duplicable, and gamut (color range) covered by a CRT depends on performance of its phosphor technology

32


Color

Christian Breiteneder


The RGB Color Model



Direct and Reflected Light



2. The CMY Color Model



$$\begin{bmatrix} R \\ G \\ B \end{bmatrix} = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix} - \begin{bmatrix} C \\ M \\ Y \end{bmatrix}$$


- another related model, CMYK, uses black as 4th color:

$$K = \min(C, M, Y), C = C - K, M = M - K, Y = Y - K$$

The HSV Color Model

- HSV: “hue saturation value”; based on tint, shade, tone model; defines a hexcone geometry
- V=1: top of cone, bright pure color; V=0: bottom of cone, Black
- H: angle around vertical axis; red = 0 deg, green = 120 deg, ...; complementary colors are 180 degrees from one another
- S = 0: centre line (V axis), S =1 side of cone
- can convert between RGB and HSV using formulae
 - subcubes of RGB fit down the cone
 - tools (xv, Photoshop, Fractal Painter) give both sets of controls to define color

The HSV Color Model




37

Color

Christian Breiteneder

The HSV Color Model



38

Color

Christian Breiteneder

Color Models (Spaces) Overview

- ❑ CIE color space (Commission Internationale de l'Eclairage)
used to calibrate other color models
1931 CIE XYZ, *tristimulus* theory
- ❑ RGB — for video display drivers
- ❑ HSB — hue (dominant color), saturation (amount of gray),
brightness (intensity)
- ❑ CMYK — cyan, magenta, yellow, black, (*subtractive primaries*)
- ❑ YUV — used in television industry, Y (luminance), UV (color
difference signals)

39


Color Models

Christian Breiteneder

Media Type Image—Example

image descriptor = {

image width = 640
image height = 480
image depth = 24
color model = RGB
encoding = YUV 8:2:2, JPEG}



40


Example

Christian Breiteneder


Image Representations

- ❑ number of channels — dim. of color model plus alpha channels
- ❑ channel depth — number of bits-per-pixel
- ❑ alpha — controls transparency; masks and blends
- ❑ pixel aspect ratio
- ❑ interlacing
- ❑ compression — lossless vs. lossy
- ❑ indexing — colors are represented by index in *color maps* or *color lookup tables* [CLUT]; map predefined or part of image

Color Display



Color Mapping



Some Image Formats

- ❑ EPS — Encapsulated PostScript
- ❑ GIF — Graphics Interchange Format
CompuServe Information Service, originally for dialup lines
- ❑ Group 3 and Group 4 Facsimile
- ❑ PICT — may contain geometric data (lines, polygons, etc.)
- ❑ JPEG — Joint Photographic Experts Group, lossy


Image Operations

- ❑ editing — “paintbrush operations,” selection
- ❑ point operations — e.g. thresholding, color correction
- ❑ filtering — also values of neighboring pixels used
- ❑ compositing — alpha channels frequently used
- ❑ geometric transformations — e.g. scaling, warping
- ❑ conversions — e.g. format conversion, color separation

Broadcasting History

- 1893 Telephone Audio Broadcasting (Puskas)
- 1895 Wireless Communication (Marconi, Popov)
- 1819 Radio Broadcasting (The Netherlands, Canada)
- 1935 TV Broadcasting (Germany, Britain)
- 1941 US b&w TV
- 1953 US color TV (NTSC)
- 1963 geostationary satellites
- mid '70s fiber optic transmission
- 1989 HDTV broadcasting (Japan)
- 1996 ATSC - digital TV standard

I.2 Media Type Video




Video is a
sequence of
FRAMES

Standards Groups

- ❑ ITU - International Telecommunication Union (formerly CCITT)
- ❑ SMPTE - Society of Motion Picture and Television Engineers
- ❑ MPEG - Motion Picture Experts Group
- ❑ ATSC - Advanced Television Systems Committee
- ❑ CCIR - Consultative Committee for International Radio
- ❑


Video Display Scanning

- analog video is a continuous signal that drives a CRT




- video composed of luminance and chroma signals

Analog Video Signals



Interlaced Fields



Characteristics of Analog Video

- frame rate (25, ~30)
- scan lines (525, 625, >1000)
- aspect ratio (4:3, 16:9)
- interlacing (2:1, non-interlaced = progressive)
- signal quality (consumer, professional, broadcast)

Characteristics of Analog Video

- ☐ composite versus component
- ☐ stability (editing degradation)
- ☐ audio tracks
- ☐ tape size

Analog Video Signal Formats

- ☐ NTSC (National Television Systems Committee): North America, Central America and Japan, and some parts of the South Pacific and South Africa.
- ☐ PAL (Phase Alternation Line): western Europe, India, China, Australia, and parts of Asia and South America.
- ☐ SECAM (Séquentiel Couleur avec Mémoire): France, Eastern Europe, Russia, and parts of Africa and the Middle East.
- ☐ RGB: A component video signal format, used for computer displays. No single RGB standard.
- ☐ HDTV (High Definition Television): The earliest HDTV system, Japan's Hi-Vision, is used for daily broadcasts in Japan (also known as MUSE)

Video Representations

- ☐ component video
 - each primary is sent as a separate signal - RGB or a luma/chroma transformation (YUV, YIQ, YC_RC_B, ...)
 - requires more bandwidth and good synchronization
- ☐ composite video
 - signals are mixed into a single carrier wave; interference
- ☐ S-video (separated video)
 - a compromise between component and composite analog video, 2 lines, one for chroma and one for luma

Analog Video Signal Format Comparison

Signal format	Comp.	Frame rate (Hz)	Scan lines	Aspect ratio	Interlacing
NTSC	1	29.97	525	4:3	2:1
YUV 525/60	3	29.97	525	4:3	2:1
PAL	1	25	625	4:3	2:1
SECAM	1	25	625	4:3	2:1
YUV 625/50	3	25	625	4:3	2:1
RGB	3	ca. 25-75	ca. 200-1000	Varies	Usually 2:1
1125/60 (Hi-Vision, MUSE)	3	30	1125	16:9	2:1
1250/50 (HD-MAC)	3	25	1250	16:9	2:1

PAL

Phase Alternating Line

- ❑ 625 scan lines repeated 25 times per second (40msec / frame)
- ❑ interlaced scan lines divide frame into 2 fields each 312.5 lines
- ❑ approximately 20% more lines than NTSC
- ❑ YUV color model
- ❑ lines reserved for control information at the beginning of each field, only 575 lines of visible data
- ❑ each line lasts 64 μ sec (12 μ sec blanked)

Video Representations


- ❑ PAL (Phase Alternation Line)
 - $Y = 0.299R + 0.587G + 0.114B$
 - $U = 0.492(B-Y)$
 - $V = 0.877(R-Y)$
- ❑ NTSC (National Television Systems Committee)
 - $Y = 0.299R + 0.587G + 0.114B$
 - $I = 0.596R - 0.275G - 0.321B$
 - $Q = 0.212R - 0.523G + 0.311B$
- ❑ new ATSC (Advanced Television Systems Committee)
 - 1920x1080 progressive 16:9
 - 1280x720 progressive 16:9

NTSC

National Television Systems Committee

- ❑ 525 scan lines per frame, 30 frames per second (actually 29.97)
- ❑ interlaced scan lines divide frame into 2 fields each 262.5 lines
- ❑ YIQ color model
- ❑ lines reserved for control information at the beginning of each field, only 485 lines of visible data
- ❑ each line lasts 63.5 μ sec (10.5 μ sec blanked)

Analog Video Tape Formats



Composite vs. Component Video

composite video

- single electrical signal
- + easy to broadcast
- + simple cabling
- poor quality

component video

- multiple electrical signal
- difficult to broadcast
- cabling more difficult
- + good quality

examples:

RGB, YUV, Y/C

Video Production Switcher

- ❑ to produce high quality visual images - n input streams and 1 output stream (live events and post-production)
- ❑ special effects - titles, transitions, picture-in-picture, chroma-key, compositing
- ❑ implementation
 - ❑ conventional solutions use custom-designed hardware
 - ❑ modern approaches use more and more software

Video Equipment

- ❑ routing switcher (matrix switch) - nxn cross bar circuit switch; analog or digital; can switch several signals; one input can be routed to multiple outputs
- ❑ distribution amplifier - split 1 input signal to 2 or more outputs
- ❑ timebase correctors (TBCs) - reconstructs signal to remove timing errors introduced by VTR/VCR
- ❑ sync generator - master clock to provide sync pulse for all equipment
- ❑ frame (delay) buffer - to synchronize external sources
- ❑ video production switcher

Video Production Switcher

mixing


keying

blending


wipes

DVEs

key framing




Video Editing / EDL



Video Synchronization


- intra-flow synchronization (skew, jitter)




Video Time Codes

- SMPTE time code (HH:MM:SS:FF)
 - non-drop frame time code - FF in [0, 29]
 - drop frame time code - FF in [2, 29], except every tenth minute [0, 29]
- time code recorded on tape
 - LTC - longitudinal time code, recorded in audio track
 - VITC - vertical interval TC, recorded in vertical blanking
 - RCTC - rewritable consumer time code, Sony Video-8 and Hi-8

Video Studio



Video Editing Comparison



Digital Video


- ☐ analog video is a continuous signal
- ☐ digital video uses discrete numeric values
- ☐ signal is sampled
- ☐ small, discrete regions are digitized
- ☐ frame is represented by pixel array

Digital Video

Digital video “sizes”:

- ☐ “raw” digital video:
 - ☐ 20 Mbyte/sec
 - ☐ 70 Gbyte/hr
 - ☐ 1 Gbyte = 50 seconds
- ☐ “low data rate” digital video
 - ☐ 200 kbit/sec – 5 Mbit/sec
 - ☐ 1 Gbyte = 30 min – 10 hr


Pixel Arrays



CCIR 601


- ❑ digital component video - CCIR Recommendation 601
- ❑ format is obtained by sampling a component video signal
- ❑ base sampling rate 3.375 MHz
- ❑ particular member of 601 m:n:1 (multipliers of sampling base rate)
- ❑ multiplier values: 1, 2, 3 or 4

4:2:0 Sampling



- ❑ Luma sample
- ❑ Chroma sample

Line Sampling



- ❑ 4:2:2 - broadcast quality; 4:1:1 - VHS quality
- ❑ 4:2:0 - 2:1 subsampling in horizontal and vertical direction
- ❑ 4:1:1 and 4:2:2 mostly used in MPEG and JPEG


Video Block Structure

- 4:2:2 $Y_C R_C B_C$

16x16 macroblock

8x8 pixel blocks


8 bits/sample = 16 bits/pixel = 4Kbits/macroblock



- 4:1:1 $Y_C R_C B_C$

3Kbits/macroblock

12 bits/pixel



Digital Video Representations

- ❑ Digital Composite Video (D2/D3, SMPTE 244M)
 - ❑ 14.3 MB/s data rate
 - ❑ subsampled color signals 4:2:2
- ❑ Digital Component Video (D1/D5, SMPTE RP125)
 - ❑ separate signals for luminance and color
 - ❑ 27 MB/s data rate
 - ❑ subsampled color signals 4:2:2

Video Data Rate

- ❑ D1 Digital
 - ❑ $720 \times 483 = 347,760$ pixels/frame
 - ❑ 4:2:2 sampling gives 695,520 bytes/frame
 - ❑ 21 MB/sec (168 Mbs)
- ❑ ATV
 - ❑ ATV
 - ❑ 4:2:0 sampling gives 1,382,400 bytes/frame
 - ❑ 41 MB/sec (328 Mbs)

Video Formats

- ❑ Digital Betacam - 720x480; 4:2:2; CCIR 601
- ❑ Sony DV Format - 500 lines; 4:1:1; DCT-based compression
- ❑ Panasonic/JVC DV Format (DVCPPro) - similar to Sony DV but 4:2:2
- ❑ Sony Betacam SX - MPEG coding (IBBI patterns)

- ❑ DVI (Intel) PLV + RTV
- ❑ QuickTime (Apple)
- ❑ px64 / H.261 (CCITT)

Digital Video Formats

Video Format	Analog formats sampled	Sampling rate (Mhz)	Sample size	Appr. video data rate (Mbyte/sec)	Frame resolution
Digital Component (CCIR 601)	525/60 YUV 625/50 YUV	13.5	8/10	30.9, 20.6, 15.4	720 X 500 720 X 600
Digital composite	Compos. NTSC Compos. PAL	14.3 17.7	8	11.2 13.7	768 X 510 948 X 608
CIF QCIF	Various	Various	8	4.5 1.1	360 X 288 180 X 144
Digital HDTV	NA	NA	NA	ca. 125	ca. 1600 X 900

Compression


- ☐ lossy versus lossless
- ☐ real-time (symmetric)
- ☐ spatial versus temporal
- ☐ scalable
- ☐ type of source material

Operations on Digital Video

- ☐ storage and retrieval (HD, CD-ROM, RAID, DVTR)
- ☐ editing (“non-linear”)
- ☐ digital video effects (transitions, keying, compositing*..)
- ☐ conversion (e.g. NTSC \Rightarrow digital \Rightarrow PAL)
- ☐ compression, decompression


Factors Influencing Video Quality

- ☐ frame size and depth
- ☐ frame rate, key frame rate
- ☐ source material \Rightarrow algorithm
- ☐ algorithm parameters, decode time
- ☐ compressed data rate
- ☐ compressed file size



Example: “Navigable Video”

$\theta \phi$: 5 degree intervals
 72 x 36 frames
 1.5 minutes



Access Function

